


Technical Specifications / Engineering Submittals

Legrand Model Number: 646013

rev20200226

LINE DRAWING



FEATURES

Energy Metering	Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor
Metering Accuracy	ISO/IEC 62053-21 1%
Metering per Input Line	Yes
Metering per Branch Circuit Breaker	Yes
Metering per Output Receptacle	No
Remote Outlet Switching	No
Environmental Sensor Ready	Yes
Replaceable Controller	No
Compatible Sensors	Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure
Networking	Two (10/100 BaseT) Ethernet ports. Optional WiFi (802.11a/b/g/n)
Remote Management	HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC
Cascading	Yes, Max 16 PDUs can be daisy chained using a single Ethernet or USB connection
Onboard Display	Color, matrix LCD display : Voltage, current, or active power (per line or per breaker); Alarms; Configuration information (name, ratings, IP / Networking information); Auto-flip orientation
Embedded Processor	ARM Cortex A5 500MHZ (Atmel A5D21C), 16MB SPI Flash, 64MB DDR2 RAM



Technical Specifications / Engineering Submittals

Legrand Model Number: 646013

rev20200226

INPUT

Input Plug	IEC60309 32A (2P3W)
Cord Length	3 meters (9.84 feet) standard
Cord Entry	Bottom-front feed
Cable Type	IP44("splashproof")
Number of Power Cords	1
Maximum Input Current	32A
Nominal Input Voltage	230V, Single phase
Rated Input Voltage	200-240V
Input Frequency	50/60Hz
Power Capacity	6.4kVA at 200V, 7.7kVA at 240V

OUTPUT

Nominal Output Voltage	230V
Rated Output Voltage	200-240V
Receptacles (Output Connections)	(36) C13, 10A (6) C19, 16A
Securelock Support	Yes
Cord Retention	Yes
Overload Protection	(2) LEGBXA6

PHYSICAL

Color	Silver, Aluminum anodized
Unit Dimensions (WxDxH)	59mm x 50mm x 1539mm; 2.3" x 2.0" x 60.6"
Mounting	Tool-less button mount



Technical Specifications / Engineering Submittals

Legrand Model Number: 646013

rev20200226

ENVIRONMENTAL

Operating Temperature	45°C
Operating Relative Humidity	85%
Operating Elevation	0-10000ft

CONFORMANCE


Regulatory Approvals	CE, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant
Warranty	Standard 2 years manufacturer warranty

Technical Specifications / Engineering Submittals

Legrand Model Number: 646013

rev20200226

CONTROL PANEL




Technical Specifications / Engineering Submittals

Legrand Model Number: 646013

rev20200226

ELECTRICAL (ONE LINE) DIAGRAM






Technical Specifications / Engineering Submittals

Legrand Model Number: 646013

rev20200226

MECHANICAL DIAGRAM



[illegible][illegible]